

# Middle Tower

## TECHNICAL INSTRUCTION

### 6 Steps to do System Assembly:

#### Step 1) Chassis Opening:

- 1.1) Pull out the front panel. (See Figure 1)
- 1.2) Take off the 2 pcs screws. Pull the left side cover from the rear side. (See Figure 2) Find the accessory kits inside the chassis to assemble the system.



Figure 1




Figure 2




Figure 3

#### Step 2) M/B Installation:

- 2.1) Install I/O shield (from inside of case). Find the correct mounting hole for M/B, screw in standoffs, fasten M/B with the screw. (See Figure 3)
- 2.2) Install add-on-cards.

#### Step 3) 3.5" FDD & HDD Installation:

- 3.1) Remove the 3.5" FDD & HDD bracket. (See Figure 4) Mount the FDD on the 3<sup>rd</sup> hole of bracket then Screw in the HDD. (See Figure 5)
- 3.2) Slide in the 3.5 " bracket into case. (See Figure 6,7)




Figure 4




Figure 5




Figure 6

#### Step 4) CD-ROM Installation:

- 4.1) Press the slide guide on the CD-ROM. (See Figure 8)
- 4.2) Slide in the CD-ROM into the case, then screw in the driver. (See Figure 9,10)




Figure 7



Figure 8




Figure 9

#### Step 5) System Cooling Fan:(Optional)

Two 9cm fans could be screw in front plate and/or rear side.(See Figure 11, 12)




Figure 10




Figure 11




Figure 12

#### Step 6) Chassis Close:

- 6.1) Slide in the left side cover, fixed with 2 pcs screws.
- 6.2) Snap in front panel with hands, finished.